




FF

Pipe Nipple
NPTF / NPTF



TUBE FITTING PART #	HOSE FITTING PART #	END SIZE		C HEX (in.)	D DRILL (in.)	D1 DRILL (in.)	L (in.)	LL AFTER ASSY (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)		
		1 NPTF	2 NPTF						-S	-SS	-B
1/8 FF	0101-2-2	1/8-27	1/8-27	7/16	0.188	0.188	1.06	0.59	6.0	7.2	3.9
1/4 x 1/8 FF	0101-2-4	1/4-18	1/8-27	5/8	0.281	0.188	1.25	0.68	6.0	7.2	3.9
1/4 FF	0101-4-4	1/4-18	1/4-18	5/8	0.281	0.281	1.45	0.77	6.0	7.2	3.9
3/8 x 1/8 FF	0101-2-6	3/8-18	1/8-27	3/4	0.406	0.188	1.45	0.87	6.0	7.2	3.9
3/8 x 1/4 FF	0101-4-6	3/8-18	1/4-18	3/4	0.406	0.281	1.45	0.76	6.0	7.2	3.9
3/8 FF	0101-6-6	3/8-18	3/8-18	3/4	0.406	0.406	1.45	0.75	6.0	7.2	3.9
1/2 x 1/8 FF	0101-2-8	1/2-14	1/8-27	7/8	0.531	0.188	1.52	0.83		7.2	
1/2 x 3/8 FF	0101-6-8	1/2-14	3/8-18	7/8	0.531	0.406	1.70	0.89	6.0	7.2	3.9
1/2 x 1/4 FF	0101-4-8	1/2-14	1/4-18	7/8	0.531	0.281	1.70	0.90	6.0	7.2	3.9
1/2 FF	0101-8-8	1/2-14	1/2-14	7/8	0.531	0.531	1.89	0.96	6.0	7.2	3.9
3/4 x 1/4 FF	0101-4-12	3/4-14	1/4-18	1 1/8	0.719	0.281	1.78	0.96	5.5	6.6	3.5
3/4 x 3/8 FF	0101-6-12	3/4-14	3/8-18	1 1/8	0.719	0.406	1.78	0.95		6.6	
3/4 x 1/2 FF	0101-8-12	3/4-14	1/2-14	1 1/8	0.719	0.281	1.96	0.84	5.5	6.6	3.5
3/4 FF	0101-12-12	3/4-14	3/4-14	1 1/8	0.719	0.719	1.96	0.70	5.5	6.6	3.5
1 x 1/4 FF	0101-4-16	1-11 1/2	1/4-18	1 3/8	0.938	0.281	1.96	1.05			
1 x 3/8 FF	0101-6-16	1-11 1/2	3/8-18	1 3/8	0.938	0.406	1.96	1.04		5.4	
1 x 1/2 FF	0101-8-16	1-11 1/2	1/2-14	1 3/8	0.938	0.531	2.09	1.06		5.4	
1 x 3/4 FF	0101-12-16	1-11 1/2	3/4-14	1 3/8	0.719	0.719	2.09	1.04	4.5	5.4	
1 FF	0101-16-16	1-11 1/2	1-11 1/2	1 3/8	0.938	0.938	2.34	1.19	4.5	5.4	3.0
1 1/4 x 1 FF	0101-16-20	1 1/4-11 1/2	1-11 1/2	1 3/4	1.250	0.938	2.45	1.28	3.0	3.6	
1 1/4 FF	0101-20-20	1 1/4-11 1/2	1 1/4-11 1/2	1 3/4	1.250	1.250	2.48	1.29	3.0	3.6	
1 1/2 x 1 FF	0101-16-24	1 1/2-11 1/2	1-11 1/2	2	1.500	0.938	2.55	1.38	3.0	3.6	
1 1/2 FF	0101-24-24	1 1/2-11 1/2	1 1/2-11 1/2	2	1.500	1.500	2.61	1.42	3.0	3.6	
2 x 1 1/2 FF	0101-24-32	2-11 1/2	1 1/2-11 1/2	2 1/2	1.500	1.500	2.79	1.58		2.4	
2 FF	0101-32-32	2-11 1/2	2-11 1/2	2 1/2	1.938	1.938	2.83	1.61	2.0	2.4	

Note: All steel "FF" fittings have a 30° chamfer for sealing with NPSM swivel type fittings.

Dimensions and pressures for reference only, subject to change.

